

## First Choice High Cover P.V.A

**First Choice High Cover P.V.A** is an economical P.V.A. formulated mainly for the contracting market. First Choice High Cover P.V.A has good all round properties i.e. obliteration, filling, drying and overcoating.

### USES:

First Choice High Cover P.V.A. is an economical first coater for raw plaster walls, or as a first and final coating for ceilings. This product is used extensively on low cost housing projects.

### SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

Ensure all surfaces to be painted are clean and free from dust, moisture, grease, etc. When used as a primer on raw plaster, apply one or two coats of First Choice High Cover P.V.A., depending on porosity of the surface. For ceilings apply one coat of First Choice High Cover P.V.A as a primer coat and finish with two coats of First Choice High Cover P.V.A. Allow the First Choice High Cover P.V.A. to dry for  $\pm 4$  hours before overcoating.

### PROPERTIES:

APPLICATION: Brush, Roller

CLEANING SOLVENT: Water

THINNING SOLVENT: Water

SPREADING RATE: PRIMER COAT : 4-6 m<sup>2</sup> per litre

FINAL COAT : Depending on porosity of surface,  $\pm 4-6$  m<sup>2</sup> per litre

DRYING TIMES: SURFACE DRY : 1 hour

HARD DRY : 4 hours

OVERCOATING : 4 hours

PACK SIZE: 5L, 20L (200L on request)

COLOUR RANGE: White

VISCOSITY: 128-130 KU

RELATIVE DENSITY: 1,40  $\pm$  0,05 kg per litre