

WARRIORSABS DECORATORS ACRYLIC

Warrior SABS Decorators Acrylic is a general purpose high hiding washable matt paint with excellent durability and has been formulated to meet the requirements of SABS 1586:1995 GRADE 3 specifications for Emulsion Paints.

USES:

Warrior sabs Decorators Acrylic can be used for interior and exterior masonry surfaces. It can also be used on suitably primed metal and wood surfaces as a topcoat.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM (H2)

- a) On new surfaces prime as follows: Masonry - Warrior Alkali Resistant Plaster Primer
Wood - Warrior White Wood Primer and Warrior Universal Undercoat
Metal – Warrior Metal Etch Primer
- b) Finish with 2 coats of Warrior sabs Decorators Acrylic allowing 4 hours drying time between coats.
- a) On previously painted surfaces: Ensure that all surfaces are suitably prepared and dry before painting. Apply 2 coats of Warrior sabs Decorators Acrylic allowing 4 hours drying time between coats.

PROPERTIES:

APPLICATION:	Brush, Roller and Spray*
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Water
SPREADING RATE:	PRIMER COAT: 4-6 m ² per litre FINAL COAT: 6-8 m ² per litre
DRYING TIMES:	SURFACE DRY: 1 hour HARD DRY: 4 hours OVERCOATING: 4 hours
PACK SIZES:	1L, 5L, 20L
COLOUR RANGE:	White only
SPECIFIC GRAVITY:	1.40 ± 0.05 kg per litre
VISCOSITY:	120-130 Krebb Units (KU)
MASS SOLIDS:	50-55%
REFLECTANCE:	>85%

GENERAL INFORMATION:

*For spray application consult our Technical Department.

- a) Please refer to the SABS 1586:1995 Specification on Emulsion Paints for a more detailed specification on Grade 3 paint.
- b) It is important that this product be thoroughly mixed with a flat paddle before use.