

WARRIORSABS UTILITY ACRYLIC

Warrior SABS Utility Acrylic is a utility grade matt acrylic paint with good filling and obliterating properties. It has been formulated to meet the requirements of SABS 1586:1995 GRADE 4 specifications for Emulsion Paints.

USES:

Warrior SABS Utility Acrylic is recommended for interior use only. It is ideal for use on projects where an economic finish with limited washability is required. It can also be use as a first coater on raw plaster or as a ceiling paint.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

On new plaster: Apply one coat Warriorfill™ or Warrior SABS Utility Acrylic. Allow to dry for ± 3 hours. Thereafter apply two coats Warrior SABS Utility Acrylic allowing 3-4 hours drying time between coats.

PROPERTIES:

APPLICATION:	Brush, Roller and Spray*
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Water
SPREADING RATE:	PRIMER COAT: 4-6 m ² per litre FINAL COAT: 6-8 m ² per litre
DRYING TIMES:	SURFACE DRY: 1 hour HARD DRY: 4 hours OVERCOATING: 4 hours
PACK SIZES:	1L, 5L, 20L
COLOUR RANGE:	White only
SPECIFIC GRAVITY:	1.5 \pm 0.05 kg per litre
VISCOSITY:	120-130 Krebb Units (KU)
MASS SOLIDS:	60-65%
REFLECTANCE:	>85%

GENERAL INFORMATION:

*For spray application consult our Technical Department.

a) Please refer to the SABS 1586:1995 Specification on Emulsion Paints for a more detailed specification on Grade 1 paint.

b) It is important that this product be thoroughly mixed with a flat paddle before use.