



**TDS 1.4**  
**WARRIOR ELEGANT COAT**

**DESCRIPTION:**

Warrior Elegant Coat is a washable and durable low odour coating with enhanced stain resistance and a subtle sheen. Warrior Elegant Coat is guaranteed for a period of 12 years subject to the terms and conditions of the Warrior Twelve Year Guarantee.

**USES:**

Warrior Elegant Coat is an excellent paint to be used in high traffic areas where cleanliness and stain resistance is of importance. It may be used either as an interior or exterior paint, but should not be used in bathrooms or kitchens.

**SPECIFICATION OR RECOMMENDED PAINT SYSTEM:**

- a) New Masonry Surfaces: All surfaces must be dry, free of dust, dirt, grease and other surface contamination. Apply one coat of Warrior Water Based Alkali Resistant Plaster Primer and allow to dry for 4-6 hours. Finish with 2 coats of Warrior Elegant Coat to colour of choice.
- b) Previously Painted Masonry Surfaces: Remove by scraping, wire brushing or sanding all soft powdered, blistered, loose or flaking paint. All surfaces should be washed and allowed to dry. All bare patches must be primed with Warrior Water Based Alkali Resistant Plaster Primer. All metal areas/nail heads, etc. should be spot primed with Warrior Metal Etch Primer.
- Gloss or sheen paints must always be sanded down with a fine abrasive to provide a good key for subsequent coats and then primed with one coat of Warrior Universal Undercoat.
- Finish off with 2 coats of Warrior Elegant Coat to colour of choice. Allow 4 hours drying time between coats.

**PROPERTIES:**

APPLICATION:	Brush, Roller and Spray*
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	PRIMER COAT: N/A TOP COATS: ± 8-10 m <sup>2</sup> per litre per coat
DRYING TIMES:	SURFACE DRY: 1 hour TOUCH DRY: 4 hours OVERCOATING: 4 hours
SCRUB RESISTANCE:	Washable surface (>10 000 Oscillations)
PACK SIZE:	1L, 5L, 20L
COLOUR RANGE:	White, Pastel, Medium, Deep and Clear Colours
RELATIVE DENSITY	1, 32 ± 0, 05 kg per litre
VISCOSITY:	100-110 KU
FLASH POINT:	Non flammable
FINISH:	Sheen



**GENERAL INFORMATION:**

\*For spray application consult our Technical Department.

- a) It is important that this product be thoroughly mixed with a flat paddle before use.
- b) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.
- c) Do not wash the paint for 7 days after painting.

**DISCLAIMER**

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

---

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)  
45 FRANS DU TOIT STREET  
P O BOX 911-1181  
ROSSLYN 0200  
SOUTH AFRICA

HELP DESK  
EMAIL: [info@warriorpaints.co.za](mailto:info@warriorpaints.co.za)  
TEL: +27 12 5413596  
FAX: +27 12 541 1434  
[www.warriorpaints.co.za](http://www.warriorpaints.co.za)