



TDS 3.2
WARRIORFILL™ / CEILING PAINT

DESCRIPTION:

Warriorfill™ is a heavy bodied acrylic fillercoat/primer with good filling and obliterating properties. It is quick drying and can be easily applied by brush or roller.

USES:

Warriorfill™ is an excellent first coater for raw plaster walls and ceilings. It is also used as an interior ceiling finishing coat. It is a heavy bodied water based paint with excellent obliteration and filling properties.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

Ensure all surfaces to be painted are clean and free from dust, moisture, grease, etc. Apply one primer coat and allow to dry for 3-4 hours before overcoating.

PROPERTIES:

APPLICATION:	Brush, Roller or Spray
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	PRIMER COAT: Depending on porosity of surface ± 4-6 m ² per litre TOP COATS: 6 m ² per litre per coat
DRYING TIMES:	SURFACE DRY: 1 hour TOUCH DRY: 3-4 hours OVERCOATING: 4 Hours
PACK SIZE:	5L, 20L
COLOUR RANGE:	White only
SPECIFIC GRAVITY:	1, 50 ± 0, 05 kg per litre
VISCOSITY:	120-130 KU
FLASH POINT:	Non flammable
FINISH:	Matt



GENERAL INFORMATION:

- a) If this product is used as a finishing coat on ceilings, all bare metal areas (e.g. nail heads) must first be primed with Warrior Metal Etch Primer.
- b) It is important that this product be thoroughly mixed with a flat paddle before use.
- c) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za