



TDS 5.4

WARRIOR INTERIOR/EXTERIOR CLEAR BRICK DRESSING

DESCRIPTION:

Warrior Interior/Exterior Clear Brick Dressing is a synthetic resin based masonry coating which is simple to use, quick drying, and offers excellent resistance to yellowing and alkaline attack. It enhances the natural colour and restores depth to brickwork, ensuring an attractive gloss and long lasting finish.

USES:

Warrior Interior/ Exterior Clear Brick Dressing can be applied to brick surfaces.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

New masonry surfaces: Ensure that the surface is dry, free from all forms of dirt, sand and loose plaster or cement. Apply the first coat thinned 10-15% by volume with Turps. To finish apply two coats of Warrior Brick Dressing as supplied to the surface allowing 8 hours drying time between coats.
For maintenance painting apply one coat when required.

PROPERTIES:

APPLICATION:	Brush, Roller, and Spray*
CLEANING SOLVENT:	Mineral Turpentine
THINNING SOLVENT:	Mineral Turpentine
SPREADING RATE:	PRIMER COAT: 6-8m ² per litre TOP COATS: 8-10m ² per litre
DRYING TIMES:	SURFACE DRY: 1 hour TOUCH DRY: 8 hours OVERCOATING: 8 hours
PACK SIZE:	1L, 5L
COLOUR RANGE:	Clear only
FLASH POINT:	>35°C
VISCOSITY:	35 ± 5 sec F4
SPECIFIC GRAVITY:	0,85 ± 0,05 kg per litre
FINISH:	Gloss



GENERAL INFORMATION:

*For spray application, contact our Technical Department.

- a) Do not apply this product to surfaces which are continually damp.
- b) Surfaces must be completely dry as any residual moisture in the substrate can result in blistering.
- c) It is important that this product be thoroughly mixed with a flat paddle before use.
- d) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za