



TDS 10.7
FIRST CHOICE SUPER SHEEN

DESCRIPTION:

First Choice Super Sheen is a low odour pure acrylic coating with a medium sheen finish. It is a durable, washable good quality paint. First Choice Super Sheen is guaranteed for a period of 10 years subject to the terms and conditions of the Warrior Ten Year Guarantee.

USES:

First Choice Super Sheen Acrylic is an excellent paint to be used in high traffic areas where cleanliness is of importance. It may be used either as an interior or exterior paint but should not be used in bathrooms or kitchens.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

- a) New Masonry Surfaces: All surfaces must be dry, free of dust, dirt, grease and other surface contamination. Apply one coat of First Choice Water Based Alkali Resistant Plaster Primer and allow to dry for 4-6 hours.
Finish with at least 2 coats of First Choice Super Sheen to colour of choice.
- b) Previously Painted Masonry Surfaces: Remove by scraping, wire brushing or sanding all soft powdered, blistered, loose or flaking paint. All surfaces should be washed and allowed to dry. All bare patches must be primed with First Choice Water Based Alkali Resistant Plaster Primer and in the case of boards or panels, all metal areas/nail heads, etc. should be spot primed with Warrior Metal Etch Primer or Warrior One Pack Etch Primer.
Gloss or semi-gloss surfaces must always be sanded down with a fine abrasive to provide a good key for subsequent coats. Enamel surfaces should be sanded and primed with one coat of First Choice Universal Undercoat.
Finish off with at least 2 coats of First Choice Super Sheen Acrylic to colour of choice.

PROPERTIES:

APPLICATION:	Brush, Roller and Spray*
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	PRIMER COAT: N/A TOP COATS: ± 8-10 m ² per litre
DRYING TIMES:	SURFACE DRY: 1 hour HARD DRY: 4 hours OVERCOATING: 4 hours
SCRUB RESISTANCE:	Washable surface (>10 000 Oscillations)
PACK SIZE:	1L, 5L, 20L
COLOUR RANGE:	White, Pastel, Medium, Deep, Clear and standard colours
RELATIVE DENSITY	1, 28 ± 0, 05 kg per litre
VISCOSITY:	100-110 KU
FLASH POINT:	Non flammable



GENERAL INFORMATION:

*For spray application consult our Technical Department.

- a) For new work or a change in colour, at least two finishing coats are normally recommended.
- b) It is important that this product be thoroughly mixed with a flat paddle before use.
- c) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

DISCLAIMER

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)
45 FRANS DU TOIT STREET
P O BOX 911-1181
ROSSLYN 0200
SOUTH AFRICA

HELP DESK
EMAIL: info@warriorpaints.co.za
TEL: +27 12 5413596
FAX: +27 12 541 1434
www.warriorpaints.co.za