



**TDS 10.9**  
**FIRST CHOICE TEXTURED COATING**

**DESCRIPTION:**

First Choice Textured Coating is a flexible exterior acrylic textured coating, which contains mica and marble. First Choice Textured Coating is guaranteed for a period of 10 years subject to the terms and conditions of the Warrior Ten Year Guarantee.

**USES:**

First Choice Textured Coating is suitable for bridging hairline cracks. It contracts and expands with the substrate guarding against harsh weather conditions. It is also used on uneven surface areas to give an even textured finish.

**SPECIFICATION OR RECOMMENDED PAINT SYSTEM:**

New Masonry Surfaces: All surfaces must be sound, dry, free of dust, dirt, grease and other surface contamination. Apply one coat of First Choice Water Based Alkali Resistant Plaster Primer or one coat of First Choice Cement Plaster Primer and allow to dry for 4-6 hours.

Finish with 2 coats of First Choice Textured Coating to colour of choice and allow 4 hours drying time between coats.

Previously Painted Masonry Surfaces: Remove by scraping, wire brushing or sanding all soft powdered, blistered, loose or flaking paint. All surfaces should be washed and allowed to dry. All bare patches must be primed with First Choice Water Based Alkali Resistant Plaster Primer or one coat of First Choice Cement Plaster Primer and allow to dry for 4-6 hours.

In the case of boards or panels, all metal areas/nail heads, etc. should be spot primed with Warrior Metal Etch Primer and allowed to dry for 4 hours.

Gloss or semi-gloss acrylic paints must always be sanded down with a fine abrasive to provide a good key for subsequent coats. Enamel paints should be sanded and then primed with one coat of Warrior Universal Undercoat. Finish off with 2 coats of First Choice Textured Coating to colour of choice. Allow 4 hours drying time between coats.

**PROPERTIES:**

APPLICATION:	Brush, Roller
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Do not thin - ready for use
SPREADING RATE:	TOP COATS: 3-5 m <sup>2</sup> per litre
DRYING TIMES:	SURFACE DRY: 2 hours
	TOUCH DRY: 4-6 hours
	OVERCOATING: 4-6 hours
PACK SIZE:	5L, 20L
COLOUR RANGE:	White and a range of popular pastel, medium and deep colours as well as popular standard colours
VISCOSITY:	125-130 KU
FLASH POINT:	Non flammable
FINISH:	Textured, Matt
RELATIVE DENSITY	1, 48 ± 0, 05 kg per litre



**GENERAL INFORMATION:**

- a) Do not thin this product as it is ready for use.
- b) This product is not suitable for spray application.
- c) It is important that this product be thoroughly mixed with a flat paddle before use.
- d) As per standard painting practices, no painting should take place if surface or ambient temperatures are below 10°C or above 30°C. Painting should cease at 3pm or when rain is imminent.

**DISCLAIMER**

The recommendations contained herein are given in good faith and are meant as a guide for specifiers and users. They are based on laboratory tests and practical historical experience. No guarantee or warranty is implied by the recommendations contained in the Technical Data Sheet as conditions of use, application method, cleanliness and soundness of the substrate are beyond our control.

N.B. Technology may change with time necessitating changes to the Technical Data Sheet (TDS). It is the specifiers and users responsibility to ascertain that the latest TDS is being used.

---

WARRIOR PAINTS AND COATINGS (PTY) LTD (REG NO. 1987/003946/07)  
45 FRANS DU TOIT STREET  
P O BOX 911-1181  
ROSSLYN 0200  
SOUTH AFRICA

HELP DESK  
EMAIL: [info@warriorpaints.co.za](mailto:info@warriorpaints.co.za)  
TEL: +27 12 5413596  
FAX: +27 12 541 1434  
[www.warriorpaints.co.za](http://www.warriorpaints.co.za)